wahoo decks
Toll Free 877.270.9387 ▪ Phone 678.343.2317 ▪ Fax 678.343.2916
AridDek Waterproof Decking

AridDek – Product Specifications

MATERIAL	6005-T5 Series Marine Grade Aluminum {extruded for precision}
LENGTH	2' - 26' lengths for delivery 32' lengths for factory pick-up {custom cuts available}
WEIGHT	1 lb per linear foot / 2 lbs per square foot {that's approximately ½ the weight of wood}
STRENGTH	400 lbs per square foot (PSF) at 24" on-center
WIDTH **Main Boards** **Start and Finish Boards**	 6" 5 ½"

Notes

SPAN: maximum joist spacing requirements, 24" on-center

HEAT DISSIPATION: aluminum provides high thermal conductivity meaning it naturally stays cooler to the touch than traditional decking materials such as composite, pressure treated lumber, or hardwoods/softwoods

FIRE RATING: non-flammable

DRAINAGE: 1/8" downward pitch per linear foot is recommended; to prevent possible backsplash a 2" overhang beyond the header joist on the drainage side is suggested

FINISH: maintenance free powder coat finish, slip resistant surface provides traction in wet or dry conditions {available in Ash Gray or Sandstone}

CORROSION RESISTANT: will not rust or deteriorate; withstands direct ground water contact and saltwater splash; suitable for long term exposure even in the harshest environments

NON-TOXIC: non-porous material; naturally resistant to mold, mildew, and bacteria {will not foster growth environment}; does not require maintenance or harsh chemicals/sealants

DURABLE: will not split, decay, crack, or rot; low expansion / contraction coefficient; will not become brittle in extreme cold

INSECT RESISTANT: impervious to insect decay or termite damage

MEETS INTERNATIONAL BUILDING CODE: ARIDDEK MEETS OR EXCEEDS THE SPECIFICATIONS AND GUIDELINES FOR ALUMINUM STRUCTURES AS RECOMMENDED BY AA ADM 1 AND REQUIRED BY THE INTERNATIONAL BUILDING CODE - 2006